

Floralife STRIP-IT™

End-of-Season Cleaner for Greenhouse Structures, Coolers / Cooling Pads and Irrigation Systems / Water Storage Tanks and Sunblock Wash

Dissolves and Removes Heat-set Grease / Oil / Dust Deposits /
Whitewash Sunblock Coatings / Salt / Algae Deposits

Contains:
Sulphuric Acid, Ammonium Bifluoride

DIRECTIONS FOR USE

THIS PRODUCT IS A CONCENTRATE AND MUST BE DILUTED BEFORE USING

This product is a specifically formulated combination of sulfuric acid and wetting agents that effectively and safely remove whitewash coatings, algae, mildew, heat-set grease / oil / dirt, calcium and other hard water deposits.

Floralife STRIP-IT™ is recommended for end of season cleaning of structures: irrigation lines/tanks and whitewash removal to create a healthy, sanitary environment for new crops being established.

GREENHOUSES / NURSERIES, BOTANICAL GARDENS, ATRIUMS, PACKING HOUSES, BOUQUET MANUFACTURERS

Note

All plants and delicate materials must be removed from treated area prior to cleaning or removing whitewash from structures. Any contact with plants or other delicate surfaces may cause damage. Recommend wearing safety goggles and protective clothing while applying Floralife STRIP-IT™.

When making solution, add slowly to surface of solution to avoid splattering. Solution may etch glass or damage surface if allowed to dry.

EXTERIOR / INTERIOR STRUCTURES

(GREENHOUSES, STORAGE BUILDINGS, ETC.)

Remove all plants and delicate materials prior to

cleaning. Spray, mop or brush surfaces with a solution of Floralife STRIP-IT™. When cleaning large areas use large volume sprayer or pressure washer to apply Floralife STRIP-IT™ solution. **Thoroughly wet surface to be cleaned so that all areas are 100% covered. Do not allow solution to dry. Reapply to maintain wetness. (Solution may etch glass or damage surface if allowed to dry). Let stand for 3 to 5 minutes.**

Rinse all treated areas thoroughly with clean water.

WORK AREA, BENCHES, COOLERS / COOL- ING PADS, CONCRETE / GRAVEL FLOORS / SHIPPING PADS, FLOOD FLOORS

Follow interior structures cleaning directions. Apply to the underside of benches/equipment and areas subjected to continuous moisture to ensure complete cleaning. For lightly soiled areas use a mop or brush to apply. Allow to soak for 3 - 5 minutes. Rinse all treated areas thoroughly with clean water.

IRRIGATION LINES/DITCHES AND STORAGE TANKS

Use this procedure only when irrigation system or storage water areas are isolated from the crop. Direct contact of Floralife STRIP-IT™ with plant material will cause phytotoxicity and possible loss of plants. It is important to prepare a solution of Floralife STRIP-IT™ by using exact recommended rates for irrigation lines and storage tanks for safe removal of algae and salt deposits.

Fill irrigation lines or add the solution directly to water in the storage tank and allow solution to sit for 8 - 12 hours. Flush system with clean water until there is no visible soap foam at the farthest end of the line. If dosing Floralife STRIP-IT™ into the lines use a higher recommended dilution and let sit for 1 - 2 hours only then flush system with clean water.

Storage water tanks should be drained and rinsed. Remove any large debris prior to filling with fresh water.

WHITEWASH SUNBLOCK COATING REMOVAL

Use large volume sprayer or pressure washer to apply Floralife STRIP-IT™ solution for whitewash removal. Thoroughly wet surface to be cleaned or stripped with the Floralife STRIP-IT™ solution so that all the areas are 100% covered.

Allow the Floralife STRIP-IT™ solution to remain wet on surface 3 - 5 minutes. Do not allow solution to dry. Reapply to maintain wetness. (Solution may etch glass or damage surface if allowed to dry).

Use a pressure washer or high pressure hose for easy rinsing and removal of whitewash. Use plenty of water to remove all traces of the Floralife STRIP-IT™ solution.

APPLICATION METHODS

High-pressure sprayers or pressure washers are recommended for removal of deposits and white wash and for rinsing. Low-pressure sprayer, mop or brush may be used for lightly soiled areas.

Follow recommended use directions. Safe to use on structures, floors, benches, coolers and equipment composed of materials such as aluminum, copper, galvanized steel, glass, plastics, polycarbonate,

Keep Out of Reach of Children /
Mantenga los productos fuera del
alcance de niños

WARNING / AVISO

If you do not understand the label, find someone to explain it to you in detail. (Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle.)

fiberglass and concrete. DO NOT allow use of Floralife STRIP-IT™ to dry on aluminum, tin, galvanized iron, glass, etc. or etching may occur. Rinse thoroughly.

Conversion Chart

3 teaspoons (tsp) = 1 tablespoon (T)
6 teaspoons (tsp) = 1 ounce (oz)
2 tablespoons (T) = 1 ounce (oz)
4 cups = 1 quart (qt)
4 quarts (qts) = 1 gallon (gal)

PRECAUTIONARY STATEMENTS / FIRST AID

SEE MATERIAL SAFETY DATA SHEET

Causes severe burns. Avoid contact with skin and eyes. Wear suitable gloves. Wear eye protection. Avoid breathing spray, mist or vapors.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15 - 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye and get medical attention.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of soap and water.

IF SWALLOWED: Administer milk of magnesia or lime water and proceed to a hospital/doctor immediately for treatment advice and/or call a poison control center. Do not give bicarbonate of soda.



Floralife, inc.

751 Thunderbolt Drive • Wallerboro, SC 29488
800-323-3689 • 800-471-4248 Fax
www.floralife.com
info@floralife.com

#6160, 6161

FLORALIFE STRIP-IT™ DILUTION TABLE

Areas of Use	Dilution Rates (fl. oz. Floralife Strip-It™ / 1 gallon water)
Exterior structures, including pipes and drains	4.0 - 13.0 fl. oz.
Interior structures, including floors, benches, coolers / cooling pads	3.0 - 5.0 fl. oz.
Greenhouse whitewash removal	10.0 - 13.0 fl. oz.
Cleaning irrigation lines	1.5 - 3.0 fl. oz. *higher dilution for dense application only
Storage tanks	1.5 - 2.5 fl. oz.